

Section 1: Chemical Product and Company Identification

EMERGENCY TELEPHONE MANUFACTURER'S NAME

Isola Group INFOTRAC U.S.-Canada: 800-535-5053

6565 West Frye Road 3100 Chandler, Arizona 85226

> Information: (852)2485-7761

Safety Data Sheet Competent Person: Eva Ho eva.ho@isola-group.com

REVISION DATE: July 19, 2020

IS400 PREPREG PRODUCT NAME: FORMULA: N/A (Product is an Article)

PRODUCT USE: Resin impregnated woven fiberglass used in the manufacture or copper-clad laminate for

printed circuit boards.

Section 2: Hazards Identification

Regulation (EC) No 1907/2006 and 29 CFR 1910.1200

GHS Hazard Classification Not a hazardous substance or mixture according to the Globally Harmonized System (GHS)

Hazard Pictogram(s): None Signal word: None Hazard Statement: None Precautionary Statement(s): None

Other Hazards: No Data Available

Section 3: Composition, Information on Ingredients

Product Composition	CAS No.	EC Inventory No.	Approx. %	Hazard Statements
Non-Respirable Woven	65997-17-3	266-046-0	35-60	None
Continuous Filament Glass Fiber	03777-17-3			
Reacted Bisphenol A-Based	VVV VV VVV	-	20-55	None
Epoxy Resin Matrix	XXX-XX-XXX			
Proprietary Fillers	XXX-XX-XXX	XXX-XX-X	10-20	STOT RE 1; H372

Section 4: First Aid Measures

INHALATION: Remove to fresh air. If not breathing, provide artificial respiration. Get

medical attention if necessary and treat symptomatically.

Wash skin with soap and water. Get medical attention if irritation persists. SKIN CONTACT: EYE CONTACT:

Flush eyes with plenty of water as a precaution. If persistent irritation

develops, seek medical attention.

INGESTION: Rinse mouth thoroughly with water. Never give anything to an

unconscious person. Get medical attention if symptoms occur.

Most important symptoms and effects, both acute and delayed:

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed:

No Data Available. Treat symptomatically.

Part No. IS400 PREPREG SDS Page 1 of 6



Section 5: Fire-fighting Measures

FLASH POINT: Not applicable FLAMMABLE LIMITS IN AIR (% by vol): Not applicable

EXTINGUISHING MEDIA: Foam, Dry Chemical Powder, or Carbon Dioxide

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus for firefighting if necessary.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Thermal decomposition or combustion may give off toxic fumes, gases and vapors.

Section 6: Accidental Release Measures

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

Prevent dust formation. Ensure adequate ventilation and isolate area. Wear proper protective equipment as specified in Section 8. Do not breathe dust or fumes/vapor from heated product.

ENVIRONMENTAL PRECAUTIONS:

No special environmental precautions required.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANUP:

Wear proper protective equipment as specified in Section 8: Exposure Controls/Personal Protection.

If material is released or spilled, sweep, shovel or vacuum material and place in closed containers for subsequent reuse or disposal.

DISPOSAL METHOD:

Disposal should be made in accordance with federal, state and local regulations.

REFERENCE TO OTHER SECTIONS: See Sections 8 and 13.

Section 7: Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Store in a cool dry place. Avoid excessive heat and ignition sources. Further processing of solid materials may result in the formation of combustible dusts. The potential for combustible dust formation should be taken into consideration before additional processing occurs. Provide appropriate exhaust ventilation at places where dust is formed.

INFORMATION ON EMPTIED CONTAINER: Not applicable

SPECIFIC USES: Resin impregnated woven fiberglass used in the manufacture or copper-clad laminate for printed circuit boards.

Section 8: Exposure Controls/Personal Protection

EXPOSURE CONTROLS:

VENTILATION:

Provide general ventilation and local exhaust ventilation to meet TLV requirements of individual ingredients and to control dusting conditions. If cutting or rimming with power equipment then dust collectors and local ventilation should be used. Avoid unnecessary exposure to dust and handle with care. Keep work area clean of dust and fibers by using an industrial vacuum cleaner with high efficiency filter or wetting down area with water. Never use compressed air and avoid dry sweeping.

EYE PROTECTION:

Wear safety glasses with side shields. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

RESPIRATORY PROTECTION:

Respiratory protection is not required. Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN 143) dust masks. Use a NIOSH/MSHA or European Standard (EN) approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or the CEN European Standards (EU).

Part No. IS400 PREPREG SDS Page 2 of 6



PROTECTIVE GLOVES:

Glove use is recommended. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with glove contamination. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

SKIN PROTECTION:

Suitable protective clothing to prevent skin contact is recommended.

WORK/HYGIENE PRACTICES:

Provide good personal hygiene after handling. Avoid contact with eyes. Wash hands after handling.

OTHER EQUIPMENT:

Make safety shower, eyewash stations, and hand washing equipment available in the work area.

CONTROL PARAMETERS:

Component	CAS No.	Value	Control Parameters	Basis		
Proprietary Fillers	XXX-XX-XXX	TWA	20 Million particles per cubic foot	USA. Occupational Exposure Limits		
	remarks	Based on impinger samples counted by light-field techniques. Containing less than 1% quartz; if 1% quartz or more, use quartz limit. mppcf x 35.3 = million particles per cubic meter = particles per c.c				
		TWA	2 mg/m3	USA. NIOSH Recommended Exposure Limits		
		TWA	2 mg/m3	USA. ACGIH Threshold Limit Values (TLV)		
		Lower Respiratory Tract irritation Pulmonary function				
		Pulmonary fibrosis The value is for particulate matter containing no asbestos and < 1% crystalline silica. Not classifiable as a human carcinogen.				
		PEL	2 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		
		See section 5208				
	xxx-xx-xxx	TWA	20Million particles per cubic foot	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts		
	remarks	Based on impinger samples counted by light-field techniques. mppcf x 35.3 = million particles per cubic meter = particles per c.c				
		TWA	80mg/m3 / %SiO2	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts		
		TWA	6 mg/m3	USA. NIOSH Recommended Exposure Limits		
		PEL	6 mg/m3	California permissible exposure limits for chemical contaminants (Title 8, Article 107)		

Part No. IS400 PREPREG SDS Page 3 of 6



Section 9: Physical and Chemical Properties

APPEARANCE - COLOR: PHYSICAL STATE:

Solid N/A

PRODUCT CRITERIA

ODOR:

	PRODUCT CRITERIA	
ODOR THRESHOLD	Not Available for product	
PH	Not Available for product	
FLASH POINT:	Not Available for product	
LOWER EXPLOSIVE LIMIT; UPPER EXPLOSIVE LIMIT	Not Available for product	
FLAMMABILITY (Solid, gas)	Not Available for product	
EXPLOSIVE PROPERTIES	Not Available for product	
OXIDIZING PROPERTIES	Not Available for product	
SPECIFIC GRAVITY (@25 °C):	Not Available for product	
EVAPORATION RATE:	Not Available for product	
% VOLATILE by VOLUME	Not Available for product	
PARTITION COEFFICIENT	Not Available for product	
AUTO IGNITION TEMPERATURE	Not Available for product	
DECOMPOSITION TEMPERATURE	Not Available for product	
BOILING POINT:	Not Available for product	
MELTING POINT:	Not Available for product	
VAPOR PRESSURE	Not Available for product	
VAPOR DENSITY (AIR = 1)	Not Available for product	
SOLUBILITY IN WATER:	Insoluble	
WATER SOLUBILITY IN THE SOLVENT	Not Available for product	
FREEZING POINT:	Not Available for product	
VISCOSITY	Not Available for product	
VOC CONTENT	Not Available for product	

OTHER INFORMATION

None

Section 10: Stability and Reactivity

REACTIVITY: Stable under normal storage conditions.

CHEMICAL STABILITY: Stable under recommended storage conditions

POSSIBILITY OF HAZARDOUS REACTIONS: No data available.

CONDITIONS TO AVOID: Exposure to excessive heat, flames, sparks and other ignition sources as well as moist air and water. Avoid incompatible materials. Avoid excessive dust generation.

INCOMPATIBLE MATERIALS: Avoid contact with strong oxidizing agents, strong acids, strong bases, mercaptans and amines.

HAZARDOUS DECOMPOSITION PRODUCTS: Dense smoke, acrid vapors and fumes, aliphatic and aromatic hydrocarbons of variable composition, CO_X , NO_X . Decomposition products depend on temperature, air supply and other materials that may be present. Uncontrolled exothermic reactions of epoxy resins release phenolics, carbon monoxide and water.

Section 11: Toxicological Information

There is no toxicological information available for the product (article) itself.

Section 12: Ecological Information

There is no ecological information available for the product (article) itself.

Part No. IS400 PREPREG SDS Page 4 of 6



Section 13: Disposal Considerations

Dispose according to local, state, and national regulations.

Section 14: Transport Information

DOT TRANSPORT: Not Regulated

ADR = International Carriage of Dangerous Goods by Road Not Regulated

RAIL TRANSPORT: Not Regulated

SEA TRANSPORT: IMDG Not Regulated

AIR TRANSPORT: IATA/ICAO Not Regulated

Section 15: Regulatory Information

OSHA HAZARD COMMUNICATION STANDARD

This product is a not "Hazardous Chemical" as defined by 29 CFR 1910.1200.

TOXIC SUBSTANCES CONTROL ACT (TSCA) STATUS:

This product is in compliance with all rules, regulations, and orders of TSCA.

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III (EPCRA) SECTIONS 311 AND 312: None

SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986 (SARA) TITLE III (EPCRA) SECTION 313 SUPPLIER NOTIFICATION: None

CALIFORNIA PROPOSITION 65:

This regulation requires a warning for California Proposition 65 chemical(s) under the statute.

The California proposition 65 chemical(s) contained in this product are: None.

CANADA:

This MSDS contains all of the information required by the Controlled Products Regulations (CPR).

WHMIS-INFORMATION:

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR), SOR/88-66. The classes of controlled products listed in the CPR, Section 32, Part IV, have been reviewed and based on Professional Judgment this product has been determined to not be WHMIS controlled.

EUROPEAN UNION:

This product has been reviewed for compliance with the following European Community Directives: REACH 1907/2006; Regulation (EC) No 1272/2008 on classification, labeling and packaging (CLP) of substances and mixtures.

Section 16: Other Information

Revision Comments: Initial version (August 1, 2004)

Revision Number: 5 (July 19, 2020)

Previous Revisions: April 23, 2018 (4); March 16, 2015 (3); November 18, 2008 (2); December 6, 2005(1)

Information Sources: REACH, OSHA 29CFR 1910.1200, Manufacturer SDSs.

FOR INDUSTRIAL USE ONLY

Disclaimer: This product is an ARTICLE as defined in the applicable regulations. This SDS document is generated to distribute health, safety and environmental data. It is not a specification sheet and none of the displayed data should be construed as a specification. Information on this SDS sheet was obtained from sources which we believe are reliable, and we believe that the

Part No. IS400 PREPREG SDS Page 5 of 6

isola

information is complete and accurate. However, the information is provided without any warranty, express or implied, regarding its correctness. Some of the information presented and conclusions drawn are from sources other than direct test data of the substance. The conditions or methods of handling, storage, use, and disposal of the product are beyond our control and may also be beyond our knowledge. It is the user's responsibility to determine the suitability of any material for a specific purpose and to adopt such safety precautions as may be necessary. If the product is used as a component in another product, this SDS information may not be applicable. For these reasons, we do not assume any responsibility and expressly disclaim liability for any loss, damage, or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.

Part No. IS400 PREPREG SDS Page 6 of 6